

TRACK FLOOR COVERING

classificazione al fuoco
resistance against fire
clasificación al fuego
classement feu

Bfl-s1

aspetto - aspect - aspecto - aspect

piano - flat - plano - plat

composizione
composition
composición
composition

60% fibra polipropilenica - 20% fibra poliammidica - 20% fibra poliestere
60% PP - 20% PA - 20% PES
60% fibra de polipropileno - 20% fibra poliamídica - 20% fibra de poliester
60% fibre de polypropylène - 20% fibre de polyamide - 20% fibre de polyester

impregnazione - soakage
impregnación - enduction

parziale - partial
parcial - partielle

peso totale - total weight
peso total - poids total


1.350 g/m2

dimensione pezze
size of the rolls
medida piezas
dimension des pièces


h. cm 200 x ml 30 - h. cm 400 a richiesta per quantitativo minimo
h. cm 200 x ml 30 - h. cm 400 on demand for minimum quantities
h. cm 200 x ml 30 - h. cm 400 a petición de una cantidad mínima
h. cm 200 x ml 30 - h. cm 400 sur demande selon quantité minimum á definir

destinazione
use
utilización
utilisation


traffico intenso, scuole, banche, negozi, uffici, alberghi, ristoranti, mostre,
esposizioni, locali pubblici, cinema
heavy traffic, schools, banks, offices, shops, hotels, restaurants, shows, exposi-
tions, public buildings, cinemas
tráfico intenso, bancos, escuelas, oficinas, tiendas, hoteles, restaurantes,
salones, exposiciones, locales públicos, cines
trafic intensif, banques, écoles, bureaux, boutiques, hotels, restaurants, exposi-
tions, salons, locaux publics, cinemas



1



2



3



9



8



6



12*

IN ESAURIMENTO



OFFICE

*Si riserviamo il diritto di apportare ai nostri prodotti, senza preavviso, ogni modifica necessaria
Nous nous réservons le droit d'apporter à nos produits, sans préavis, toute modification nécessaire
Nos reservamos el derecho de modificar nuestros productos, sin previo aviso*

 **Techin**

www.techin.it
info@techin.it
338.2564843

Via Schiavonia 76 - 31022 PREGANZIOL - TV