



# GRANITO

## FLOOR COVERING

classificazione al fuoco  
resistance against fire  
clasificación al fuego  
classement feu

Bfl

composizione - composition  
composición - composition

100% PA

fondo  
backing  
soporte  
dossier

Juta Sintetica  
action backing  
jute sintético  
jute synthétique

numero punti/m2  
number of knots/m2  
número de puntos/m2  
nombre de points/m2

173.360

antistatico permanente (+/- volt):  
permanently antistatic (+/- volt):  
antiestático permanente (+/- volt):  
antistatique permanent (+/- volt):

ISO 6356 ≤ 2000

solidità alla luce  
lightfastness  
resistencia a la luz  
solidité à la lumière

ISO 105 B02 2000 ≥ 6

solidità del colore allo sfregamento a secco  
rubbingfastness dry  
resistencia al refregamiento seco  
solidité au frottement sec

ISO 105 X12 2001 ≥ 4

solidità del colore allo sfregamento a umido  
rubbingfastness wet  
resistencia al refregamiento húmedo  
solidité au frottement humide

ISO 105 X12 2001 ≥ 4

solidità colori all'acqua cambio colore  
waterfastness change in colour  
resistencia colores al agua - cambio colores  
solidité de coloris à l'eau - changement de coloris

ISO 105 E01 2002 ≥ 4

solidità colori all'acqua sfumatura colore  
waterfastness staining  
resistencia colores al agua - gradación colores  
solidité à l'eau - nuance coloris

ISO 105 E01 2002 ≥ 4

grado d'assorbimento acustico  
sound absorption  
absorción acústico  
absorption phonique

ISO 354 ± 0,15

resistenza termica (in m2/KW)  
thermal retention  
resistencia térmica  
résistivité thermique

DIN 52612 ≤ 0,062

peso felpa - pile weight  
peso fibra - poids fibre

460 g / m2

peso totale - total weight  
peso total - poids total

1.630 g/m2 (+/- 15%)

spessore totale - total thickness  
espesor total - épaisseur total

5,00 mm ca

dimensione pezza  
length of the rolls  
medida piezas  
dimension des pièces

ml 25/30 ca x h.cm 200/400  
(h.cm 500 a richiesta per minimo 500 m2)  
disponibile in tappeti su misura con o senza orlatura a filo  
(h.cm 500 for minimum quantity of 500 m2)  
available in mats made to measure with or without overlocking  
(h.cm 500 para cantidades mínimas de 500 m2)  
disponible en alfombras a la medida con o sin festones a hilo  
(h.cm 500 par quantité minimum de 500 m2)  
disponible en tapis sur mesure avec ou sans bords surjetés

 Techin.it

